

HydroCover™ – #089779 Wood Blend



TriFlo™ — makes the best hydraulic mulch even better!

- Improves moisture retention
- Improves the suspension of mulch, seed and fertilizer within the slurry and prevents the dewatering of the fiber mulch
- Improves the application of hydraulic mulch in a more uniform layer for better coverage and enhanced product performance
- Improves application efficiency by increasing shooting distance and enhancing hose performance—greatly reducing downtime associated with clogging



The ultimate in blend performance...

- 100% Thermally Refined® wood fiber with the highest quality cellulose mulch in the industry
- Delivers up to 15% greater yield to contractors versus competitive blend products
- Covers up to 20% more ground than 100% cellulose and provides superior erosion control and more complete germination without a jump in price
- Enhances water-holding capacity, reducing soil erosion while improving turf coverage
- Provides superior erosion control and germination performance compared to 100% cellulose fiber
- Non-toxic, environmentally safe and biodegradable
- Maximum slope length of 23 feet
- Use approved mechanically agitated equipment for optimum pumping and application performance
- HydroCover™ Blend functional longevity is \leq 3 months



Product Composition:

Thermally Refined® Wood Fibers (minimum) – 60%
Cellulose Fiber (maximum) – 28%
Moisture Content – 12% \pm 3%
(40) 50-lb bales per pallet

Slope Gradient/Condition

\leq 4H:1V
> 4H:1V and \leq 3H:1V

Rate

2000 lb/acre
2500 lb/acre

