



SoilCover® Wood Fiber

Now with TriFlo™! — makes the best hydraulic mulch even better!

- Improves moisture retention
- Improves the suspension of mulch, seed and fertilizer within the slurry and prevents the dewatering of the fiber mulch
- Improves the application of hydraulic mulch in a more uniform layer for better coverage and enhanced product performance
- Improves application efficiency by increasing shooting distance and enhancing hose performance—greatly reducing downtime associated with clogging



Creates an interlocking matrix for enhanced erosion control protection!

Our experience and expertise result in your success

Each SoilCover® product is created with the knowledge of what makes plants grow and unequalled experience in what makes you successful. Our Thermally Refined® wood fiber is a prime example — holding 13.5 times its weight in water and improving yield. The process that produces Thermally Refined wood fiber uses heat and pressure to break wood down into more fibrous material with greater surface area.

- SoilCover® Wood Fiber holds up to 50% more water than competitor products
- 100% Thermally Refined wood fiber allows for enhanced seed survival rates due to higher moisture retention within the matrix
- Creates a near perfect environment for faster germination
- SoilCover Wood Fiber creates an interlocking matrix for better erosion control protection and allows for improved oxygen transfer
- Greater productivity — eliminates clogs from the coarse fiber found in competitive mulches
- Non-toxic, environmentally safe and biodegradable
- Maximum slope length of 28 feet
- Use approved mechanically agitated equipment for optimum pumping and application performance
- SoilCover Wood Fiber functional longevity is ≤ 3 months



Product Composition:

Thermally Refined® Wood Fibers – 100%
(40) 50-lb bales per pallet

<u>Slope Gradient/Condition</u>	<u>Rate</u>
≤ 4H:1V	2000 lb/acre
> 4H:1V and ≤ 3H:1V	2500 lb/acre
> 3H:1V and ≤ 2H:1V	3000 lb/acre

